



# Consumer unit S · EV · flush-mounted

Flat or small house up to about 80 m<sup>2</sup> with one kitchen, with an electric vehicle (EV): a dedicated 11 kW charger circuit with a Type B RCD.

## PLN 4,956.90

incl. 23% VAT · PLN 4,030.00 excl. VAT · excluding delivery

|           |                                                                                                                                   |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------|
| Size      | <b>Size S — flat or small house up to approx. 80 m<sup>2</sup>, about 10 circuits</b>                                             |
| Enclosure | <b>48-module enclosure — room for the EV charger; one size up from the Standard version (36 modules), same number of circuits</b> |

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

10 circuits in 2 groups of 4-pole Type A RCDs (30 mA), induction hob on a 3-phase circuit, T1+T2 surge protection. An 11 kW EV charger on a dedicated 3-phase circuit with a Type B RCD — required for chargers without DC leakage detection. 48-module enclosure (4 rows × 12) — room for the EV charger; one size up from the Standard version (36 modules), same number of circuits. Devices take 35 — 27% spare.

### MOUNTING AND DIMENSIONS

|                           |                                                                      |
|---------------------------|----------------------------------------------------------------------|
| Mounting                  | <b>flush-mounted — back box built into the wall, frame with door</b> |
| Wall opening              | <b>366 × 780 mm, depth 89 mm</b>                                     |
| Minimum wall thickness    | <b>110 mm</b>                                                        |
| Frame with door (visible) | <b>396 × 810 mm</b>                                                  |

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).

### CONTENTS

48-module enclosure · 4 rows · devices take 35

|                                                                                       |         |
|---------------------------------------------------------------------------------------|---------|
| Main switch, surge protection device, phase indicators, N/PE terminal bars            | 8 mod.  |
| 4-pole Type A residual current devices (RCDs) × 2 (circuit groups)                    | 8 mod.  |
| Circuit breakers (MCBs) × 10 (sockets, lighting, appliances; induction hob — 3-phase) | 12 mod. |
| Flush-mounted enclosure (back box for building into the wall, frame with door)        | —       |
| EV charging — 11 kW                                                                   | 7 mod.  |
| Type B RCD for the charger                                                            | —       |

### SPECIFICATIONS

|                                                                                                     |                                                 |
|-----------------------------------------------------------------------------------------------------|-------------------------------------------------|
| DIN modules: <b>35 used of 48 (spare 13)</b>                                                        | Circuits: <b>10 (max. 18 in this enclosure)</b> |
| Residual current devices (RCDs): <b>2 × 4-pole 40 A, 30 mA, Type A — circuits split into groups</b> |                                                 |
| Surge protection device (SPD): <b>T1+T2</b>                                                         |                                                 |

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.co.uk/products/s-ev?mounting=flush>



# Consumer unit S · EV · flush-mounted

## CIRCUITS AND RCD GROUPS

Typical set of circuits for this size (board model shared by the shop and the workshop). Cable sizes are indicative — selected by length and installation method.

Circuit names and the diagram are in Polish.

| Ref. | Circuit / load                      | Protection | Poles | Phase | Cable | RCD |
|------|-------------------------------------|------------|-------|-------|-------|-----|
| F1   | Oświetlenie — strefa dzienna        | B10        | 1P    | L2    | 3×1,5 | Q1  |
| F2   | Gniazda — salon                     | B16        | 1P    | L1    | 3×2,5 | Q1  |
| F3   | Piekarnik                           | B16        | 1P    | L1    | 3×2,5 | Q1  |
| F4   | Zmywarka                            | B16        | 1P    | L3    | 3×2,5 | Q1  |
| F5   | Łazienka — gniazda                  | B16        | 1P    | L2    | 3×2,5 | Q1  |
| F6   | Gniazda — kuchnia (blat)            | B16        | 1P    | L3    | 3×2,5 | Q2  |
| F7   | Płyta indukcyjna (3-fazowa)         | B16        | 3P    | L1–L3 | 5×2,5 | Q2  |
| F8   | Pralka                              | B16        | 1P    | L2    | 3×2,5 | Q2  |
| F9   | Oświetlenie — sypialnie i korytarz  | B10        | 1P    | L1    | 3×1,5 | Q2  |
| F10  | Gniazda — sypialnie                 | B16        | 1P    | L3    | 3×2,5 | Q2  |
| F11  | Ładowarka samochodu (wallbox) 11 kW | B16        | 3P    | L1–L3 | 5×4   | Q3  |


## RCD GROUPS

- Q1 RCD 4P 40 A 30 mA typ A: F1, F2, F3, F4, F5
- Q2 RCD 4P 40 A 30 mA typ A: F6, F7, F8, F9, F10
- Q3 RCD 4P 40 A 30 mA typ B (ładowarka): F11

Schemat jednokreskowy – Consumer unit S · EV · flush-mounted

marka wg dostępności · podtynkowa · nr wzór

Zasilanie z licznika: 3/N/PE ~ 400/230 V 50 Hz · sieć TN-C-S · zabezpieczenie przedlicznikowe gG / B ≤ 32 A (typowo 25–32 A, wg warunków przyłączenia)



| Oznaczenie     | FV1   | H1     | F1    | F2    | F3    | F4    | F5    | F6    | F7    | F8    | F9    | F10   | F11   |
|----------------|-------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Zabezpieczenie | T1+T2 | —      | B10   | B16   | B16   | B16   | B16   | B16   | B16   | B16   | B10   | B16   | B16   |
| Bieguny        | 3+1   | 3 × 1P | 1P    | 1P    | 1P    | 1P    | 1P    | 1P    | 3P    | 1P    | 1P    | 1P    | 3P    |
| Faza           | L1–L3 | L1–L3  | L2    | L1    | L1    | L3    | L2    | L3    | L1–L3 | L2    | L1    | L3    | L1–L3 |
| Przewód [mm²]  | —     | —      | 3×1,5 | 3×2,5 | 3×2,5 | 3×2,5 | 3×2,5 | 3×2,5 | 5×2,5 | 3×2,5 | 3×1,5 | 3×2,5 | 5×4   |
| Moc szac. [kW] | —     | —      | 0,4   | 1,5   | 3     | 2     | 2     | 2     | 7,2   | 2,2   | 0,3   | 1     | 11    |

Odbiornik

- Ogranicznik przepięć → PE
- Lampki obecności fazy
- Oświetlenie – strefa dzienna
- Gniazda – salon
- Piekarnik
- Zmywarka
- Lazienka – gniazda
- Gniazda – kuchnia (blat)
- Płyta indukcyjna (3-fazowa)
- Pračka
- Oświetlenie – sypialnie i korytarz
- Gniazda – sypialnie
- Lądowarka samochodów (wallbox) 11 kW

Svalcon · Consumer unit S · EV · flush-mounted

Nr wzór · marka wg dostępności · obudowa – (4 × 12 mod.)

Wersja karta 2026-10-14 · 2026-10-25 · arkusz 1/1

SZKIC – do weryfikacji przez elektryka uprawnionego