



Consumer unit S · EV · door: tinted glass

Flat or small house up to about 80 m² with one kitchen, with an electric vehicle (EV): a dedicated 11 kW charger circuit with a Type B RCD.

PLN 5,252.10

incl. 23% VAT · PLN 4,270.00 excl. VAT · excluding delivery

Size	Size S — flat or small house up to approx. 80 m², about 10 circuits
Enclosure	48-module enclosure — room for the EV charger; one size up from the Standard version (36 modules), same number of circuits

Some items have a preliminary price (new in our range) — we will confirm it when we check your order.

10 circuits in 2 groups of 4-pole Type A RCDs (30 mA), induction hob on a 3-phase circuit, T1+T2 surge protection. An 11 kW EV charger on a dedicated 3-phase circuit with a Type B RCD — required for chargers without DC leakage detection. 48-module enclosure (4 rows × 12) — room for the EV charger; one size up from the Standard version (36 modules), same number of circuits. Devices take 35 — 27% spare.

MOUNTING AND DIMENSIONS

Mounting	surface-mounted — enclosure on the wall
Enclosure dimensions	336 × 750 × 151 mm (W × H × D)

Approximate dimensions — we confirm them against the data sheet of the selected enclosure in the order confirmation (before you cut the recess).

CONTENTS

48-module enclosure · 4 rows · devices take 35

Main switch, surge protection device, phase indicators, N/PE terminal bars	8 mod.
4-pole Type A residual current devices (RCDs) × 2 (circuit groups)	8 mod.
Circuit breakers (MCBs) × 10 (sockets, lighting, appliances; induction hob — 3-phase)	12 mod.
Door: tinted glass	—
EV charging — 11 kW	7 mod.
Type B RCD for the charger	—

SPECIFICATIONS

Door: **Tinted glass — White frame with tinted glass — you can see the LEDs and device status without opening the door.**

DIN modules: **35 used of 48 (spare 13)**

Circuits: **10 (max. 18 in this enclosure)**

Residual current devices (RCDs): **2 × 4-pole 40 A, 30 mA, Type A — circuits split into groups**

Surge protection device (SPD): **T1+T2**

Lead time: 5–10 working days from receipt of the deposit.

Included: wiring diagram, circuit chart, test report, EU declaration of conformity, 24-month warranty. Built to EN 61439-3 (PN-EN 61439-3). Technical documents are issued in Polish.

<https://svalcon.co.uk/products/s-ev>



Consumer unit S · EV · door: tinted glass

CIRCUITS AND RCD GROUPS

Typical set of circuits for this size (board model shared by the shop and the workshop). Cable sizes are indicative — selected by length and installation method.

Circuit names and the diagram are in Polish.

Ref.	Circuit / load	Protection	Poles	Phase	Cable	RCD
F1	Oświetlenie — strefa dzienna	B10	1P	L2	3×1,5	Q1
F2	Gniazda — salon	B16	1P	L1	3×2,5	Q1
F3	Piekarnik	B16	1P	L1	3×2,5	Q1
F4	Zmywarka	B16	1P	L3	3×2,5	Q1
F5	Łazienka — gniazda	B16	1P	L2	3×2,5	Q1
F6	Gniazda — kuchnia (blat)	B16	1P	L3	3×2,5	Q2
F7	Płyta indukcyjna (3-fazowa)	B16	3P	L1–L3	5×2,5	Q2
F8	Pralka	B16	1P	L2	3×2,5	Q2
F9	Oświetlenie — sypialnie i korytarz	B10	1P	L1	3×1,5	Q2
F10	Gniazda — sypialnie	B16	1P	L3	3×2,5	Q2
F11	Ładowarka samochodu (wallbox) 11 kW	B16	3P	L1–L3	5×4	Q3


RCD GROUPS

- Q1 RCD 4P 40 A 30 mA typ A: F1, F2, F3, F4, F5
- Q2 RCD 4P 40 A 30 mA typ A: F6, F7, F8, F9, F10
- Q3 RCD 4P 40 A 30 mA typ B (ładowarka): F11

Schemat jednokreskowy – Consumer unit S · EV · door: tinted glass

marka wg dostępności · natynkowa · nr wzór

Zasilanie z licznika: 3/N/PE ~ 400/230 V 50 Hz · sieć TN-C-S · zabezpieczenie przedlicznikowe gG / B ≤ 32 A (typowo 25–32 A, wg warunków przyłączenia)



Oznaczenie	FV1	H1	F1	F2	F3	F4	F5	F6	F7	F8	F9	F10	F11
Zabezpieczenie	T1+T2	—	B10	B16	B16	B16	B16	B16	B16	B16	B10	B16	B16
Bieguny	3+1	3 × 1P	1P	1P	1P	1P	1P	1P	3P	1P	1P	1P	3P
Faza	L1–L3	L1–L3	L2	L1	L1	L3	L2	L3	L1–L3	L2	L1	L3	L1–L3
Przewód [mm²]	—	—	3×1,5	3×2,5	3×2,5	3×2,5	3×2,5	3×2,5	5×2,5	3×2,5	3×1,5	3×2,5	5×4
Moc szac. [kW]	—	—	0,4	1,5	3	2	2	2	7,2	2,2	0,3	1	11

Odbiornik

- Ogranicznik przepięć → PE
- Lampki obecności fazy
- Oświetlenie – strefa dzienna
- Gniazda – salon
- Piekarnik
- Zmywarka
- Lazienka – gniazda
- Gniazda – kuchnia (blat)
- Płyta indukcyjna (3-fazowa)
- Pračka
- Oświetlenie – sypialnie i korytarz
- Gniazda – sypialnie
- Lądowarka samochodów (wallbox) 11 kW

Svalcon · Consumer unit S · EV · door: tinted glass

Nr wzór · marka wg dostępności · obudowa – (4 × 12 mod.)

Wersja karta 2026-10-14 · 2026-10-25 · arkusz 1/1

SZKIC – do weryfikacji przez elektryka uprawnionego